










適合圧砕機

SK3500Dで使用

SK2200Dで使用

ニブラー型式	KR3000R	KR2000TPR	KR2150TPR	KR1600TPR	KS1300TPR	KR1200PR-2	KR1100PR-2	KR1000LPR-2 (強化型)	
圧砕機質量	18,000	19,300	9,800	12,000	11,700	4,900	4,150	2,940	
									
A 最大開口時全長	4,750	5,590	3,860	4,460	4,260	3,070	2,545	2,600	
B 全幅	4,250	3,520	2,770	2,910	2,580	2,000	1,720	1,700	
C 直径	Ø1,720	Ø1,870	Ø1,450	Ø1,600	Ø1,600	Ø990	Ø830	Ø860	
D 開口幅	3,000	2,000	2,150	1,600	1,330	1,150	1,100	1,000	
E カッタ長さ	なし	750	300	600	940	200	200	350	
圧砕力	先端	3,330 {340}	2,744 {280}	2,208 {225}	1,991 {203}	2,256 {230}	1,275 {130}	1,030 {105}	843 {86}
	中央	6,566 {670}	3,783 {386}	3,410 {348}	2,716 {277}	4,148 {423}	2,029 {207}	1,670 {170}	1,314 {134}
取付寸法	アーム先端幅	600	800	553	600	600	450	306~325	325
	ピン径	Ø150	Ø190	Ø130	Ø150	Ø150	φ100	φ80	φ80
使用油圧 MPa{kgf/cm ² }	30.9 {315}	30.9 {315}	29.4 {300}	29.4 {300}	29.4 {300}	29.4 {300}	34.3 {350}	29.4 {300}	